

# 300 Elevation Table



This handsomely crafted and extremely durable table is the elevation version of our 300 Stationary. Adjustable height is operated at the touch of a foot switch and allows you to optimally position each patient, thereby facilitating your adjustment and saving your back over time! Shown with Metal Elevation (Oak Elevation is optional).

**NOTE:** Elevation tables are eligible for a significant tax credit under the **IRS Disabled Access Tax Credit** (Form 8826).

## COLORS

Black, Navy Blue, Burgundy and Espresso  
Custom Colors are also available

## HEIGHT CHOICES

### Metal or Oak Vertical Lift without Wheels

20"-30" / 21"-31" / 22"-32" / 23"-33"

### Metal Vertical Lift with Wheels

20.5"-30.5" / 21.5"-31.5" / 22.5"-32.5" / 23.5"-33.5"

### Oak Vertical Lift with Wheels

20" - 30" / 21" - 31"

## OPTIONS

Headpiece Lateral Motion

Thoracic Drop & Incline

Pelvic Drop

Ankle Rest Elevation

Metal or Red Oak Elevation

Locking Wheels

## ACCESSORIES

Crescent Arm Rest

Comfort Pillow

Headpiece Extension Pillow

Side Arm Rests (not adjustable)

Electrical Cord Cover

Custom Logo



**THULI TABLES**

800.458.4854 / 608.935.9300

608.935.9192 Fax

[www.thulitables.com](http://www.thulitables.com)

[office@thulitables.com](mailto:office@thulitables.com)

[facebook.com/thulitables](https://facebook.com/thulitables)

[youtube.com/thulitables](https://youtube.com/thulitables)

## 300 ELEVATION FEATURES

### Headpiece

- Flexion: 0 - 20°, Extension: 0 - 15°
- Vertical Elevation: 0 - 6.5" (0 - 17 cm)
- Straight Drop and Forward Motion Drop: 0.62" (16 mm) drop height, adjustable tension
- Lateral Motion (optional): 0 - 20° right and left
- Compound angle possible, locks into position
- Contoured cushions are adjustable in width at front end, 3.25" thick: 0.5" soft foam laminated to 2.75" firm foam
- Paper Hanger, Hold-Down and Tear-Off Bar, One roll of headpiece paper (8.5") provided

### Prone Arm Rest

- Adjustable position

### Thoracic Drop & Incline (optional)

- Drop height of 0.7" (18 mm) at front, adjustable tension
- Inclines to fixed 20° / 5.5" (14 cm) height at front. Does not drop in inclined position.
- 16" x 20"

### Pelvic Drop (optional)

- Drop height of 0.7" (18 mm) front, adjustable tension
- 20" x 20"

### Ankle Rest Elevation & Extension

- Adjustable Extension: 0 - 11" (0 - 28 cm), locks into position
- Adjustable Elevation (optional): 0 - 6" (0 - 15 cm)
- 7" x 20"

### Hand Cocking Levers / Tension Control

- Cocking levers on both sides of table
- Adjustable tension control on one side (patient's right while prone)

## 300 ELEVATION SPECIFICATIONS

**Base Size:** 19" x 39" (48 - 99 cm)

**Table Length:** 68" - 79" (173 - 201 cm), with Ankle Rest extended

**Table Width:** 20" (51 cm)

**Wheels (optional):** Locking and swiveling, 3" diameter, non-marking polyurethane

**Weight:** 210 lbs (96 kgs)

**Table Frame:** Red Oak wood, interlocking joints, durable varnish

**Base Construction:** Metal or Metal Encased in Oak, 19" x 39"

**Foam:** 3.25" (8.3 cm) thick, medium firm, high resiliency

**Upholstery:** Tailored sewn Naugahyde vinyl

**Drop Mechanism:** Adjustable compression spring, stainless steel plunger in high density polyethylene housing

**Box sizes:** 56" x 25" x 22" (145 x 64 x 56 cm)

28" x 22" x 16" (71 x 56 x 41 cm)

**Shipping weight:** 250 lbs (114 kgs, Metal) or 275 lbs (125 kgs, Oak)

**Assembly Time:** 30 minutes, tools included. Shipped partially disassembled to insure maximum protection in transit and to reduce shipping expense.

## ELECTRIC LIFT MOTOR SPECIFICATIONS

**Weight capacity:** 900 lbs (409 kgs)

**Vertical Travel:** 0 - 10" (0 - 25 cm), quiet & smooth

**Vertical Speed:** Approx. 1" (2.5 cm) per second

**Construction:** Swiss-engineered & manufactured, aluminum telescoping columns, worm-gear linear drive

**Electrical:** 110 or 230 Volts

**Switch:** Electropneumatic foot switch (black)

**Electrical Cord:** 10 ft hospital-grade cordset with ground, Grey

**Cord Cover:** 6 ft, Grey (optional)

**Warranty:** Limited Lifetime