

350 Elevation Table



This handsomely crafted and extremely durable table is the elevation version of our 300 Stationary. Adjustable height is operated at the touch of a foot switch and allows you to optimally position each patient, thereby facilitating your adjustment and saving your back over time! Shown with Metal Elevation (Wood Elevation is optional).

NOTE: Elevation tables are eligible for a significant tax credit under the **IRS Disabled Access Tax Credit** (Form 8826).

COLORS

Black, Navy Blue, Burgundy and Espresso
Custom Colors are also available

HEIGHT CHOICES

Metal or Wood Vertical Lift without Wheels
20"-30" / 21"-31" / 22"-32" / 23"-33"

Metal Vertical Lift with Wheels
20.5"-30.5" / 21.5"-31.5" / 22.5"-32.5" / 23.5"-33.5"

Wood Vertical Lift with Wheels
20" - 30" / 21" - 31"

OPTIONS

Headpiece Lateral Motion
Ankle Rest Elevation
Metal or Wood Elevation
Locking Wheels

ACCESSORIES

Locking Wheels
Electrical Cord Cover
Custom Logo
Crescent Arm Rest
Comfort Pillow
Bolsters (small & large)
Headpiece Extension Pillow
Prone Arm Rest Shields



THULI TABLES

800.458.4854 / 608.935.9300
608.935.9192 Fax
www.thulitables.com
office@thulitables.com
facebook.com/thulitables
youtube.com/thulitables

350 ELEVATION FEATURES

Headpiece

- Flexion: 0 - 20°, Extension: 0 - 15°
- Vertical Elevation: 0 - 6.5" (0 - 17 cm)
- Straight Drop and Forward Motion Drop: 0.62" (16 mm) drop height, adjustable tension
- Lateral Motion (optional): 0 - 20° right and left
- Compound angle possible, locks into position
- Contoured cushions are adjustable in width at front end, 2.75" thick: 0.5" soft foam laminated to 2.25" firm foam
- Paper Hanger, Hold-Down and Tear-Off Bar, One roll of headpiece paper (8.5") provided

Prone Arm Rest

- Adjustable position

Thoracic Drop & Incline

- Drop height of 0.7" (18 mm) at front, adjustable tension
- Inclines to fixed 20° / 5.5" (14 cm) height at front. Does not drop in inclined position.
- 16" x 20"

Pelvic Drop

- Drop height of 0.7" (18 mm) front, adjustable tension
- 20" x 20"

Ankle Rest Elevation & Extension

- Adjustable Extension: 0 - 11" (0 - 28 cm), locks into position
- Adjustable Elevation (optional): 0 - 6" (0 - 15 cm)
- 7" x 20"

Hand Cocking Levers / Tension Control

- Cocking levers on both sides of table
- Adjustable tension control on one side (patient's right while prone)

350 ELEVATION SPECIFICATIONS

Base Size:	19" x 39" (48 - 99 cm)
Table Length:	68" - 79" (173 - 201 cm), with Ankle Rest extended
Table Width:	20" (51 cm)
Wheels (optional):	Locking and swiveling, 3" diameter, non-marking polyurethane
Weight:	Metal 210 lbs (96 kgs) or wood 220 lbs (100 kgs)
Table Frame:	Hardwood, interlocking joints, durable varnish
Base Construction:	Metal or Metal Encased in Wood, 19" x 39"
Foam:	2.5" (6.5 cm): 1.5" soft foam laminated to 1" firm foam
Upholstery:	Tailored sewn Naugahyde vinyl
Drop Mechanism:	Adjustable compression spring, stainless steel plunger in high density polyethylene housing
Box sizes:	56" x 25" x 22" (145 x 64 x 56 cm) 28" x 22" x 16" (71 x 56 x 41 cm)
Shipping weight:	Metal 245 lbs (114 kgs) or Oak 255 lbs (125 kgs)
Assembly Time:	30 minutes, tools included. Shipped partially disassembled to insure maximum protection in transit and to reduce shipping expense.

ELECTRIC LIFT MOTOR SPECIFICATIONS

Weight capacity:	900 lbs (409 kgs)
Vertical Travel:	0 - 10" (0 - 25 cm), quiet & smooth
Vertical Speed:	Approx. 1" (2.5 cm) per second
Construction:	Swiss-engineered & manufactured, aluminum telescoping columns, worm-gear linear drive
Electrical:	110 or 230 Volts
Switch:	Electropneumatic foot switch (black)
Electrical Cord:	10 ft hospital-grade cordset with ground, Grey
Cord Cover:	6 ft, Grey (optional)
Warranty:	Limited Lifetime (see website for details)