

550 Elevation Table



This office model is the elevation version of our 500 Fixed Height Table. Adjustable height is electrically operated at the touch of a foot switch and allows you to optimally position each patient, thereby facilitating your adjustment and maintaining the health of your back! The Swiss-engineered lift is smooth and quiet. With an ergonomically contoured hardwood frame, this table is unparalleled in visual appeal.

NOTE: Elevation tables are eligible for a significant tax credit, under the **IRS Disabled Access Tax Credit (Form 8826)**.

COLORS

Black, Navy Blue, Burgundy and Espresso
Custom Colors are also available

HEIGHT CHOICES

Without Wheels

18.5" - 28.5" / 19.5" - 29.5" / 20.5" - 30.5"

With Wheels

17.5" - 27.5" / 18.5" - 28.5"

ACCESSORIES

Locking Wheels
Electrical Cord Cover
Custom Logo
Crescent Arm Rest
Comfort Pillow
Bolsters (small & large)
Headpiece Extension Pillow
Prone Arm Rest Shields

550 ELEVATION FEATURES

Headpiece

- Flexion: 0 - 14°, Extension: 0 - 20°
- Vertical Elevation: 0 - 6" (0 - 15 cm)
- Straight Drop & Forward Motion Drop: 0.62" (16 mm) drop height, adjustable tension
- Lateral Motion: 0 - 25° right and left
- Compound angle possible, locks into position
- Contoured cushions are adjustable in width at front end. 2.75" thick: 0.5" soft foam laminated to 2.25" firm foam
- Paper Hanger, Hold-Down and Tear-Off Bar
One roll of headpiece paper (8.5") provided

Prone Arm Rest

- Adjustable position

Thoracic Drop

- Drop height of 0.7" (17.5 mm) at front, adjustable tension
- Does not incline
- 16" x 20" contoured

Pelvic Drop & Incline

- Drop height of 1.25" (32 mm) at front, adjustable tension
- Inclines from 0 - 20° / 0 - 6" (0 - 15 cm) at front
- Drops in inclined position
- 20" x 20"

Ankle Rest Extension & Elevation

- Adjustable Extension: 0 - 11" (0 - 28 cm), locks into position
- Adjustable Elevation: 0 - 6" (0 - 15 cm), locks into position
- 7" x 20"

Operating Levers / Tension Control

- Foot cocking pedals & fold-away hand cocking levers on both sides
- Adjustable tension control on one side (patient's right while prone)

550 ELEVATION SPECIFICATIONS

Base Size:	19" x 39" (48 x 99 cm)
Table Length:	68" - 79" (173 - 201 cm) with Ankle Rest extended
Table Width:	20" (51 cm)
Wheels (optional):	Locking and swiveling, 3" diameter, non-marking polyurethane
Weight:	220 lbs (100 kgs)
Table Frame:	Hardwood, interlocking joints, durable varnish
Base Construction:	Metal Encased in Wood, 19" x 39"
Foam:	2.25" (5.7 cm) thick, medium firm, high resiliency
Upholstery:	Tailored sewn Naugahyde vinyl
Drop Mechanism:	Adjustable compression spring, stainless steel plunger in high density polyethylene housing
Box sizes:	56" x 26" x 19" (142 x 66 x 48 cm) 28" x 22" x 16" (71 x 56 x 41 cm)
Shipping weight:	325 lbs (147 kgs)
Assembly Time:	15 minutes, tools included. Shipped partially disassembled to insure maximum protection in transit and to reduce shipping expense.

ELECTRIC LIFT MOTOR SPECIFICATIONS

Weight capacity:	900 lbs (409 kgs)
Vertical Travel:	0 - 10" (0 - 25 cm), quiet & smooth
Vertical Speed:	Approx. 1" (2.5 cm) per second
Construction:	Swiss-engineered & manufactured, aluminum telescoping columns, worm-gear linear drive
Electrical:	110 or 230 Volts
Switch:	Electropneumatic foot switch (black)
Cord:	10 ft hospital-grade cordset with ground, Grey
Cord Cover:	6 ft, Grey (optional)
Warranty:	Limited Lifetime (see website for details)

