

650 Elevation Table



The contemporary, high-tech 650 Elevation offers a smooth 10" vertical range at the touch of a foot switch, allowing you to position each patient at an ideal adjusting height while maintaining the health of your back! Extremely versatile and solid, the functional features are identical to that of our 550 Elevation.

NOTE: Elevation tables are eligible for a significant tax credit under the **IRS Disabled Access Tax Credit** (Form 8826).

COLORS

Black, Navy Blue, Burgundy and Espresso
Custom Colors are also available

HEIGHT CHOICES

Without Wheels

17.5"-27.5" / 18.5"-28.5" / 29.5"-29.5" / 20.5"-30.5"

With Wheels

18"-28" / 29"-29" / 20"-30" / 21"-31"

ACCESSORIES

Locking Wheels

Electrical Cord Cover

Custom Logo

Crescent Arm Rest

Comfort Pillow

Bolsters (small & large)

Headpiece Extension Pillow

Prone Arm Rest Shields



THULI TABLES

800.458.4854 / 608.935.9300

608.935.9192 Fax

www.thulitables.com

office@thulitables.com

facebook.com/thulitables

youtube.com/thulitables

650 ELEVATION FEATURES

Headpiece

- Flexion: 0 - 14°, Extension: 0 - 20°
- Vertical Elevation: 0 - 6" (0 - 15 cm)
- Straight Drop & Forward Motion Drop: 0.62" (16 mm) drop height, adjustable tension
- Lateral Motion: 0 - 25° right and left
- Compound angle possible, locks into position
- Contoured cushions are adjustable in width at front end, 2.75" thick: 0.5" soft foam laminated to 2.25" firm foam
- Paper Hanger, Hold-Down & Tear-Off Bar, One roll of headpiece paper (8.5") provided

Prone Arm Rest

- Adjustable position

Thoracic Drop

- Drop height of 0.7" (17.5 mm) at front, adjustable tension
- Does not incline
- 16" x 20" contoured

Pelvic Drop & Incline

- Drop height of 1.25" (32 mm) at front, adjustable tension
- Inclines from 0 - 20° / 0 - 6" (0 - 15 cm) at front
- Drops in inclined position
- 20" x 20"

Ankle Rest Extension & Elevation

- Adjustable Extension: 0 - 12" (0 - 31 cm), locks into position
- Adjustable Elevation: 0 - 6" (0 - 15 cm), locks into position
- 7" x 20"

Operating Levers / Tension Control

- Foot cocking pedals & fold-away hand cocking levers on both sides
- Adjustable tension control on one side (patient's right while prone)

650 ELEVATION SPECIFICATIONS

Base Size: 19" x 39" (48 x 99 cm)

Table Length: 68" - 80" (173 - 203 cm), with Ankle Rest extended

Table Width: 20" (51 cm)

Wheels (optional): Locking & swiveling, 3" diameter, non-marking, polyurethane

Weight: 250 lbs (114 kgs)

Base Construction: Metal

Foam: 2.25" (5.7 cm) thick, medium firm, high resiliency

Upholstery: Tailored sewn Naugahyde vinyl

Drop Mechanism: Adjustable compression spring, stainless steel plunger in high density polyethylene housing

Box sizes: 56" x 26" x 19" (142 x 66 x 48 cm)

28" x 22" x 16" (71 x 56 x 41 cm)

Shipping weight: 295 lbs (134 kgs)

Assembly Time: 15 minutes, tools included. Shipped partially disassembled to insure maximum protection in transit and to reduce shipping expense.

ELECTRIC LIFT MOTOR SPECIFICATIONS

Weight capacity: 900 lbs (409 kgs)

Vertical Travel: 0 - 10" (0 - 25 cm), quiet & smooth

Vertical Speed: Approx. 1" (2.5 cm) per second

Construction: Swiss-engineered & manufactured, aluminum telescoping columns, worm-gear linear drive

Electrical: 110 or 230 Volts

Switch: Electropneumatic foot switch (black)

Cord: 10 ft hospital-grade cordset with ground, Grey

Cord Cover: 6 ft, Grey (optional)

Warranty: Limited Lifetime (see website for details)