

Tour Conversion Base



CONVERSION BASE SPECIFICATIONS

- Length:** Base: 53" (135 cm)
With Tour attached: 66" - 72" (168 -188 cm)
- Width:** Base at widest point: 19" (48 cm)
With Tour attached: 20" (51 cm)
- Conversion Time:** Less than 5 minutes to attach or detach Tour to Conversion Base
- Base Construction:** Metal or Wood Encased
- Weight:** Metal: 130 lbs (59 kgs), Wood: 144 lbs (65 kgs)
With Tour attached: 195 - 210 lbs (88 - 95 kgs)
- Box size:** 56" x 26" x 16" (143 x 66 x 41 cm)
- Shipping Weight:** Metal: 175 lbs (80 kgs), Wood: 185 lbs (84 kgs)

ELECTRIC LIFT MOTOR SPECIFICATIONS

- Weight capacity:** 900 lbs (409 kgs)
- Vertical Travel:** 0 -10" (0 - 25 cm), quiet & smooth
- Vertical Speed:** Approx. 1" (2.5 cm) per second
- Construction:** Swiss-engineered & manufactured, aluminum telescoping columns, worm-gear linear drive
- Electrical:** 110 or 230 Volts
- Switch:** Electropneumatic foot switch (black)
- Electrical Cord:** 10 ft hospital-grade cordset with ground, Grey
- Cord Cover:** 6 ft, Grey (optional)
- Warranty:** Limited Lifetime

TABLE HEIGHT CHOICES

Metal or Wood Vertical Lift without Wheels

19"- 29" / 20"- 30" / 21"- 31" / 22"- 32"

Metal Vertical Lift with Wheels

19"- 29" / 20"- 30" / 21"- 31" / 22"- 32"

Wood Vertical Lift with Wheels

19"- 29" / 20"- 30"

OPTIONS / ACCESSORIES

Metal or Wood Vertical Elevation

Locking Wheels

Electrical Cord Cover

RETROFIT

Retrofits to all Tours built after 1990



Two tables in one! Ingeniously converts the Tour Portable to an Elevation Table in minutes. Simply fold the legs into their storage position and mount the Tour to the Conversion Base using four hand-turn knobs. Detaches quickly when the need for a portable arises.

NOTE: In the US, elevation tables are eligible for a significant tax credit, under the **IRS Disabled Access Tax Credit (Form 8826)**.



THULI TABLES

800.458.4854 / 608.935.9300

608.935.9192 Fax

www.thulitables.com

office@thulitables.com

facebook.com/thulitables

youtube.com/thulitables