

Complement your chiropractic adjusting table

This wide elevation table can be used for a varieties of therapies and/or massage. It is extremely comfortable while also offering excellent support. Available in two widths (24" or 29"). The touch of a foot switch allows each patient to be optimally positioned, while maintaining the health of your back. Accessories add increased versatility.

NOTE: Elevation tables are eligible for a significant tax credit under the IRS Disabled Access Tax Credit (Form 8826).

COLORS

Black, Navy Blue, Burgundy and Espresso Custom Colors are also available

HEIGHT CHOICES

Metal or Wood Base without Wheels 19.5"-29.5" / 20.5"-30.5" / 21.5"-31.5" / 22.5"-32.5"

Metal Base with Wheels 19.5"-29.5" / 20.5"-30.5" / 21.5"-31.5" / 23.5"-33.5"

Wood Base with Wheels 19.5"-29.5" / 20.5"-30.5"

ACCESSORIES

Adjustable Headpiece & Pillow Side Arm Rests Locking Wheels **Electrical Cord Cover**

TABLE FEATURES

Headpiece Pillow (optional)

- · Comfort Pillow mounted to an adjustable base
- · Headpiece brackets fit dowels 8" on center
- · Choice to attach to one or both ends of table
- · Easily removeable

Side Arm Rests (optional)

- · Each Arm Rest is 5" wide x 36" long
- Two per table (increasing width to 39")
- · Choice to attach to one or both ends of table
- · Easily removeable

Locking Wheels (optional)

- Swiveling & locking
- Non-marking
- · 3" diameter

Cord Cover (optional)

· Protects & conceals the on-floor electrical cord

TABLE SPECIFICATIONS

Table Length:	72" (28.5 cm)
Table Widths:	24" (61 cm) or 29" (11.5 cm)
Wheels (optional):	Locking and swiveling, 3" diameter, non-marking polyurethane
Weight:	Metal 190 lbs (88 kgs) or wood 200 lbs (91 kgs)
Base Construction:	Metal or Metal Encased in Wood
Foam:	3" (7.5 cm): 2" soft foam laminated to 1" firm foam
Upholstery:	Tailored sewn Naugahyde vinyl
Box sizes:	75" x 33" x 7" (30 x 13 x 2.5 cm)
	56" x 26" x 24" (22 x 10 x 9 cm)
Shipping weight:	~285 lbs (129 kgs)
Assembly Time:	10 minutes, tools included. Shipped partially
	disassembled to insure maximum protection in transit and to reduce shipping expense.

ELECTRIC LIFT MOTOR SPECIFICATIONS

	0 -10" (0 - 25 cm), quiet & smooth
Vertical Speed:	Approx. 1" (2.5 cm) per second
Construction:	Swiss-engineered & manufactured, aluminum
	telescoping columns, worm-geared linear drive
Electrical:	110 or 230 Volts
Switch:	Electropneumatic foot switch (black)
Electrical Cord:	10 ft hospital-grade cordset with ground, Grey
Cord Cover:	6 ft, Grey (optional)
Warranty:	Limited Lifetime (see website for details)



voutube.com/thulitables