

650 Elevation Table



The contemporary, high-tech 650 Elevation offers a smooth 10" vertical range at the touch of a foot switch, allowing you to position each patient at an ideal adjusting height while maintaining the health of your back! Extremely versatile and solid, the functional features are identical to that of our 550 Elevation.

NOTE: Elevation tables are eligible for a significant tax credit under the **IRS Disabled Access Tax Credit** (Form 8826).

COLORS

Black, Navy Blue, Burgundy and Espresso
Custom Colors are also available

HEIGHT CHOICES

Without Wheels

17.5"-27.5" / 18.5"-28.5" / 19.5"-29.5" / 20.5"-30.5"

With Wheels

17.5"-27.5" / 18.5"-28.5" / 19.5"-29.5"
20.5"-30.5" / 21.5"-31.5" / 23"-33"

ACCESSORIES

Locking Wheels
Electrical Cord Cover
Custom Logo
Crescent Arm Rest
Comfort Pillow
Bolsters (small & large)
Headpiece Extension Pillow
Prone Arm Rest Shields



THULI TABLES

800.458.4854 / 608.935.9300
608.935.9192 Fax
www.thulitables.com
office@thulitables.com
facebook.com/thulitables
youtube.com/thulitables

650 ELEVATION FEATURES

Headpiece

- Flexion: 0 - 14°, Extension: 0 - 20°
- Vertical Elevation: 0 - 6" (0 - 15 cm)
- Straight Drop & Forward Motion Drop: 0.62" (16 mm) drop height, adjustable tension
- Lateral Motion: 0 - 25° right and left
- Compound angle possible, locks into position
- Contoured cushions are adjustable in width at front end, 2.75" thick: 0.5" soft foam laminated to 2.25" firm foam
- Paper Hanger, Hold-Down & Tear-Off Bar, One roll of headpiece paper (8.5") provided

Prone Arm Rest

- Adjustable position

Thoracic Drop

- Drop height of 0.7" (17.5 mm) at front, adjustable tension
- Does not incline
- 16" x 20" contoured

Pelvic Drop & Incline

- Drop height of 1.25" (32 mm) at front, adjustable tension
- Inclines from 0 - 20° / 0 - 6" (0 - 15 cm) at front
- Drops in inclined position
- 20" x 20"

Ankle Rest Extension & Elevation

- Adjustable Extension: 0 - 12" (0 - 31 cm), locks into position
- Adjustable Elevation: 0 - 6" (0 - 15 cm), locks into position
- 7" x 20"

Operating Levers / Tension Control

- Foot cocking pedals & fold-away hand cocking levers on both sides
- Adjustable tension control on one side (patient's right while prone)

650 ELEVATION SPECIFICATIONS

- Base Size:** 19" x 39" (48 x 99 cm)
- Table Length:** 68" - 80" (173 - 203 cm), with Ankle Rest extended
- Table Width:** 20" (51 cm)
- Wheels (optional):** Locking & swiveling, 3" diameter, non-marking, polyurethane
- Weight:** 250 lbs (114 kgs)
- Base Construction:** Metal
- Foam:** 2.25" (5.7 cm) thick, medium firm, high resiliency
- Upholstery:** Tailored sewn Naugahyde vinyl
- Drop Mechanism:** Adjustable compression spring, stainless steel plunger in high density polyethylene housing
- Box sizes:** 56" x 26" x 19" (142 x 66 x 48 cm)
28" x 22" x 16" (71 x 56 x 41 cm)
- Shipping weight:** 290 lbs (132 kgs)
- Assembly Time:** 15 minutes, tools included. Shipped partially disassembled to insure maximum protection in transit and to reduce shipping expense.

ELECTRIC LIFT MOTOR SPECIFICATIONS

- Weight capacity:** 900 lbs (409 kgs)
- Vertical Travel:** 0 - 10" (0 - 25 cm), quiet & smooth
- Vertical Speed:** Approx. 1" (2.5 cm) per second
- Construction:** Swiss-engineered & manufactured, aluminum telescoping columns, worm-gear linear drive
- Electrical:** 110 or 230 Volts
- Switch:** Electropneumatic foot switch (black)
- Cord:** 10 ft hospital-grade cordset with ground, Grey
- Cord Cover:** 6 ft, Grey (optional)
- Warranty:** Limited Lifetime (see website for details)